

AMENDMENTS TO THE CLAIMS

1-3. (Cancelled)

4. (Previously Presented) A ring switchover method in a network constituted of layer 2 switches connected in a ring shape, each layer 2 switch having a path control function and a failure detection function, said ring switchover method comprising:

providing in each layer 2 switch an address learning table in which a Media Access Control (MAC) address and a corresponding port are stored;

on detection of a link failure between mutually neighboring layer 2 switches, transmitting a failure notification from packet from each neighboring layer 2 switch, and

in a layer 2 switch having received the failure notification frame, recording a Media Access Control (MAC) address of said layer 2 switch into the failure notification frame, and transferring the failure notification frame to a neighboring layer 2 switch,

wherein, when the network is separated into two network groups caused by a failure, with respect to a host address connected to an arbitrary layer 2 switch, updating path information in the address learning table in a layer 2 switch belonging to the other group than the group to which said layer 2 switch belongs, so that a packet transmission direction on the ring is shifted to a port side opposite to the direction having been used up to the present.

5. (Previously Presented) A ring switchover in a network constituted of layer 2 switches connected in a ring shape, each layer 2 switch having a path control function and a failure detection function, said ring switchover method comprising:

providing in each layer 2 switch an address learning table in which a Media Access Control (MAC) address and a corresponding port are stored;

on detection of a link failure between mutually neighboring layer 2 switches,
transmitting a failure notification from packet from each neighboring layer 2 switch, and
in a layer 2 switch having received the failure notification frame, recording a Media
Access Control (MAC) address of said layer 2 switch into the failure notification frame, and
transferring the failure notification frame to a neighboring layer 2 switch,

wherein, on receipt of the failure notification frame in a layer 2 switch having a blocking
port, said layer 2 switch stores a record, indicative of the layer 2 switch of interest having a
blocking port, into the failure notification frame, and

, wherein, when the network is separated into two network groups caused by a failure,
with respect to a host address connected to an arbitrary layer 2 switch, updating path information
in the address learning table in a layer 2 switch belonging to the other group than the group to
which said layer 2 switch belongs, so that a packet transmission direction on the ring is shifted to
a port side opposite to the direction having been used up to the present.

6.(Previously Presented) A ring switchover method in a network constituted of layer 2 switches
connected in a ring shape, each layer 2 switch having a path control function and a failure
detection function, said ring switchover method comprising:

providing in each layer 2 switch an address learning table in which a Media Access
Control (MAC) address and a corresponding port are stored;

transmitting a state notification frame from a layer 2 switch connected in the ring shape
successively to neighboring layer 2 switches;

in the neighboring layer 2 switch, detecting that the corresponding neighboring layer 2
switch is faulty when the state notification frames are not received for a predetermined number

of times;

transmitting a failure notification frame packet from the layer 2 switch having detected the failure;

recording a Media Access Control (MAC) address of a layer 2 switch having received the failure notification frame into said failure notification frame; and

transferring the failure notification frame to a neighboring layer 2 switch,

wherein, when the network is separated into two network groups caused by a failure, with respect to a host address connected to an arbitrary layer 2 switch, updating path information in the address learning table in a layer 2 switch belonging to the other group than the group to which said layer 2 switch belongs, so that a packet transmission direction on the ring is shifted to a port side opposite to the direction having been used up to the present.

7. (Original) The ring switchover method according to claim 4, wherein updating the path information in the address learning table is performed by exchanging address information related to system modification between the arbitrary layer 2 switch and the layer 2 switch belonging to the other group by use of a system switchover frame.

8. (Original) The ring switchover method according to claim 5, wherein updating the path information in the address learning table is performed by exchanging address information related to system modification between the arbitrary layer 2 switch and the layer 2 switch belonging to the other group by use of a system switchover frame.

9. (Original) The ring switchover method according to claim 6, wherein updating the path

information in the address learning table is performed by exchanging address information related to system modification between the arbitrary layer 2 switch and the layer 2 switch belonging to the other group by use of a system switchover frame.

10. (Original) The ring switchover method according to claim 7, wherein updating the path information in the address learning table is performed by transmitting either a broadcast frame in which a Media Access Control (MAC) address of a host under each layer 2 switch is set as an originating address, or a frame dedicatedly provided for updating the address learning table, at the time of a system switchover.

11. (Original) The ring switchover method according to claim 8, wherein updating the path information in the address learning table is performed by transmitting either a broadcast frame in which a Media Access Control (MAC) address of a host under each layer 2 switch is set as an originating address, or a frame dedicatedly provided for updating the address learning table, at the time of a system switchover.

12. (Original) The ring switchover method according to claim 9, wherein updating the path information in the address learning table is performed by transmitting either a broadcast frame in which a Media Access Control (MAC) address of a host under each layer 2 switch is set as an originating address, or a frame dedicatedly provided for updating the address learning table, at the time of a system switchover.